

## DS-2CD2725FHWD-IZS 2 MP IR Varifocal Dome Network Camera



### Key Features

- 1/2.8" Progressive Scan CMOS
- 1920 × 1080 @60fps
- High frame rate
- Powered by Darkfighter
- H.265, H.265+
- 120dB WDR
- IP67, IK10
- IR range: up to 30 m
- BLC/3D DNR/ROI/HLC
- Smart encoding: Support low bit rate, low latency
- 4 behavior analyses and face detection
- Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR  
Color: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR



## Specifications


| <b>Camera</b>               |  |
|-----------------------------|--|
| Image Sensor                | 1/2.8" Progressive Scan CMOS   |
| Min. Illumination           | Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR<br>Color: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR                |
| Shutter Speed               | 1/3 s to 1/100,000 s   |
| Slow Shutter                | Yes  |
| Day & Night                 | IR Cut Filter  |
| Digital Noise Reduction     | 3D DNR   |
| WDR                         | 120dB  |
| 3-Axis Adjustment           | Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 355°   |
| <b>Lens</b>                 |  |
| Focal length                | 2.8 to 12 mm   |
| Lens Type                   | Motorized  |
| Aperture                    | F1.4   |
| Focus                       | Auto   |
| FOV                         | Horizontal field of view: 105° to 35°<br>Vertical field of view: 56° to 20°<br>Diagonal field of view: 126° to 40.5° |
| Lens Mount                  | Φ14  |
| <b>IR</b>                   |  |
| IR Range                    | Up to 30 m   |
| Wavelength                  | 850nm  |
| <b>Compression Standard</b> |  |
| Video Compression           | Main stream: H.265/H.264<br>Sub stream: H.265/H.264/MJPEG<br>Third stream: H.265/H.264                               |
| H.264 Type                  | Main Profile/High Profile  |
| H.264+                      | Main stream supports   |
| H.265 Type                  | Main Profile   |
| H.265+                      | Main stream supports   |
| Video Bit Rate              | 32 Kbps to 16 Mbps   |
| Audio Compression           | G722.1/G711/G726/MP2L2/PCM   |
| Audio Bit Rate              | 64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)  |
| <b>Smart Feature-set</b>    |  |
| Behavior Analysis           | Line crossing detection, intrusion detection, unattended baggage detection, object removal detection                 |
| Exception Detection         | Scene change detection   |
| Face Detection              | Yes  |
| Region of Interest          | Support 1 fixed region for main stream and sub stream  |
| <b>Image</b>                |  |
| Max. Resolution             | 1920 × 1080  |
| Main Stream                 | 50Hz: 50fps (1920 × 1080, 1280 × 960, 1280 × 720)<br>60Hz: 60fps (1920 × 1080, 1280 × 960, 1280 × 720)               |
| Sub Stream                  | 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)  |

|                               |   |
|-------------------------------|---|
|                               | 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)   |
| Third Stream                  | 50Hz: 25fps (1920 × 1080, 1280×720, 640 × 360, 352 × 288)<br>60Hz: 30fps (1920 × 1080, 1280×720, 640 × 360, 352 × 240)                      |
| Image Enhancement             | BLC/3D DNR/HLC  |
| Image Setting                 | Rotate mode, saturation, brightness, contrast, sharpness and white balance adjustable by client software or web browser                     |
| Day/Night Switch              | Day/Night/Auto/Schedule/Triggered by Alarm In   |
| <b>Network</b>                |   |
| Network Storage               | Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR   |
| Alarm Trigger                 | Motion detection, video tampering, network disconnected, IP address conflict, illegal login, HDD full, HDD error, Alarm input, Alarm output |
| Protocols                     | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour            |
| General Function              | One-key reset, anti-flicker, three streams, heartbeat, password protection, privacy mask, watermark, IP address filter                      |
| Firmware Version              | V5.5.80   |
| API                           | ONVIF (PROFILE S, PROFILE G), ISAPI   |
| Simultaneous Live View        | Up to 6 channels  |
| User/Host                     | Up to 32 users<br>3 levels: Administrator, Operator and User  |
| Client                        | iVMS-4200, Hik-Connect, iVMS-5200, iVMS-4500  |
| Web Browser                   | Plug-in required live view: IE8+, Chrome 41.0-44, Firefox 30.0-51, Safari 8.0-11<br>Plug-in free live view: Chrome 45.0+, Firefox 52.0+     |
| <b>Interface</b>              |   |
| Audio                         | 1 input (line in, 3.5 mm), 1 output(3.5 mm), mono sound   |
| Communication Interface       | 1 RJ45 10M/100M self-adaptive Ethernet port   |
| Alarm                         | 1 input, 1 output (max. 12 VDC, 30 mA), terminal block  |
| Video Output                  | 1Vp-p composite output (75 Ω) (For adjustment only)   |
| On-board storage              | Built-in Micro SD/SDHC/SDXC slot, up to 128 GB  |
| SVC                           | H.264 and H.265 encoding  |
| Reset Button                  | Yes   |
| <b>Audio</b>                  |   |
| Environment Noise Filtering   | Yes   |
| Audio Sampling Rate           | 8kHz/16kHz/32kHz/44.1kHz/48kHz  |
| <b>General</b>                |   |
| Operating Conditions          | -30 °C to +60 °C (-22 °F to +140 °F), Humidity 95% or less (non-condensing)   |
| Power Supply                  | 12 VDC ± 25%, PoE (802.3af)<br>Terminal block for DC input  |
| Power Consumption and Current | 12 VDC, 0.75A, max. 9.5W<br>PoE (802.3af, 36V to 57V), 0.3A to 0.1A, max. 11W   |
| Protection Level              | IP67, IK10  |
| Material                      | Metal   |
| Dimensions                    | Φ153.4 × 133.1 mm (Φ6.04" × 5.24")  |
| Weight                        | Camera: 1287 g (2.84 lb.)   |

## Available Model:

DS-2CD2725FHWD-IZS

## Dimensions



## Accessories



DS-1471ZJ-155  
Pendant Mount



DS-1473ZJ-155  
Wall Mount



DS-1475ZJ-SUS  
Vertical Pole Mount



DS-1476ZJ-SUS  
Corner Mount

Distributed by



## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com